



Commercial & Industrial Softener Systems

Model	HE 1.5 Twin	HE 1.5	CTM	Hi-Flo 3E	CSM	Hi-Flo 50
						
Flow Rate (per tank)	23 - 37 GPM	23 - 37 GPM	51 - 104 GPM	160 - 280 GPM	67 - 259 GPM	108 - 400 GPM
*Capacity (per tank)	Up to 210 K	Up to 210 KGR	Up to 600 KGR	Up to 1.2 M grains per tank	Up to 900 KGR	Up to 2 M grains per tank
Pipe Size	1.5"	1.5"	1.5" & 2"	3"	2" & 3"	3" & 4"
Features						
Valve Type	Top Mount	Top Mount	Top Mount	Top Mount	Side Mount Multi-Port Diaphragm	Side Mount Valve Vest
Valve Body Material	Plastic	Plastic	Plastic	Brass	100% E-coated Cast Iron	Galvanized Steel Valve Harness
Tank Type	Fiberglass	Fiberglass	Fiberglass	Fiberglass	Steel / ASME Steel	Steel / ASME Steel
Control	Culligan Smart Controller (GBE)	Culligan Smart Controller (GBE)	Culligan Smart Controller (GBE)	Culligan Smart Controller (GBE)	Culligan Smart Controller (GBE)	Culligan Smart Controller (GBE)
Regeneration Initiation						
Time-Clock	√	√	√	√	√	√
Meter	√	√	√	√	√	√
Aqua-Sensor	√	√	√	√	√	√
Alternating	√		√	√	√	√
Duplex	√	√	√	√	√	√
Parallel		√	√	√	√	√
Progressive Flow		√	√	√	√	√
Local Wireless Remote Monitor	√	√	√	√	√	√
Central Remote Monitoring	√	√	√	√	√	√

*Capacity at 15lbs/cu. ft.